



LOGIC W L W



304 32 01 83 W

AVAILABLE IN

ALU GREY 304 32 01 83 A

ANTHRACITE (DARK GREY) 304 32 01 83 N

WHITE 304 32 01 83 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	110-135
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,5W / CRI>80 / 3000K / 1480lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1480lm // 9,5W // 156lm/W
LED TECHNICS (LUMINAIRE)	135lm // 11W // 12lm/W

Requirements


CONCRETE BOX 191

CONCRETE PACK LOGIC W L

For detailed installation instructions, please consult the manual: [**304_32_01_XX_V04_HAND.pdf**](#)

FINISH YOUR SPECIFICATION


Concrete boxes



270 11 191 CONCRETE BOX 191

☐

Concrete packs



304 32 96 CONCRETE PACK LOGIC W L

☐

Notes: