

NANOLINE W

Nanoline is a very slim and multifunctional led profile, which can be used in both interior and exterior lighting concepts. This wall mounted profile can be used for either up- or downlight, creating a cosy wall grazing effect.

www.deltalight.com/nanoline





NANOLINE W

PROFILE



NANOLINE W / LEDSTRIP WARM WHITE


NLW - PROFILE CL ◇
366 00 00 CL ◇
 ◇ = ANO
 INCL. NANOLINE - PC CLEAR

NLW - PROFILE SBL ◇
366 00 00 SBL ◇
 ◇ = ANO
 INCL. NANOLINE - PC SBL

MAX. L / PROFILE: 6m
 Kg / m

1,1

TOL EN12020-2



FULL INFO TECHNICAL CHAPTER

OPTIONS

CONTROL GEAR

24V-DC / 5A DIM1 UNIT 90 x 22 x 17
300 90 003 ED1





24V-DC / 5A DIM5 UNIT 90 x 22 x 17
300 90 003 ED5



24V-DC / 2 x 4A WIRELESS DIM UNIT 90 x 22 x 17
300 90 010



END CAP



NL - END CAP SET ◇
364 03 01 ◇
 ◇ = A
 SET OF 2 PCS

0,1


NO MODULE IN THIS AREA
 5 mm (10 mm LEDFLEX OUT)

CORNER

FIXATION

NL - FIXATION SET
364 06 11
 SET OF 10 PCS


0,1



POSITION FOR INSTALLATION

DOWN

UP



CURRENT SUPPLY

NO MODULE IN THIS AREA
 10 mm



LEDFLEX 5m - 24V-DC [0,3] 						
		WHITE		TW NEW	RGB	
		Dividable per 100mm 70 smd LED/m	Dividable per 50mm 140 smd LED/m	Dividable per 33,3mm 180 smd LED/m	Dividable per 167mm 30 smd LED/m	
		5W/m 650lm/m	15W/m 1400lm/m	22W/m 2100lm/m	14,4W/m 1350lm/m	8W/m
NEW CRI > 90						
4000 K						
	IN	LEDFLEX IN 940 300 91 52 94	LEDFLEX IN FP 940 300 91 53 94			
	OUT IP65	LEDFLEX OUT 940 300 91 62 94	LEDFLEX OUT FP 940 300 91 63 94			
3000 K						
	IN	LEDFLEX IN 930 300 91 52 93	LEDFLEX IN FP 930 300 91 53 93	LEDFLEX IN HP 930 300 91 54 93		
	OUT IP65	LEDFLEX OUT 930 300 91 62 93	LEDFLEX OUT FP 930 300 91 63 93			
2700 K						
	IN	LEDFLEX IN 927 300 91 52 92	LEDFLEX IN FP 927 300 91 53 92	LEDFLEX IN HP 927 300 91 54 92		
	OUT IP65	LEDFLEX OUT 927 300 91 62 92	LEDFLEX OUT FP 927 300 91 63 92			
2700 / 4000 K						
	IN			LEDFLEX IN TW 300 91 55 2740		
	OUT IP65					
RGB						
	IN				LEDFLEX IN RGB 300 91 52 33	
	OUT IP65				LEDFLEX OUT RGB 300 91 62 33	
FULL INFO TECHNICAL CHAPTER						
LED POWER SUPPLY 24V-DC / 20W 300 89 24 20 OPTIONS 24V-DC / 5A DIM UNIT	max.4 m	max.1 m	max.0,9 m	max.1,3 m	⊗ max.2,4 m	
LED POWER SUPPLY 24V-DC / 40W 300 89 24 40 OPTIONS 24V-DC / 5A DIM UNIT	max.8 m	max.2,5 m	max.1,8 m	max.2,7 m	⊗ max.5 m	
LED POWER SUPPLY 24V-DC / 60W 300 89 24 60 OPTIONS 24V-DC / 5A DIM UNIT	max.12 m	max.4 m (max.3m / Powerline)	max.2,7 m (max.3m / Powerline)	max.4,1 m	⊗ max.7,36 m	
LED POWER SUPPLY 24V-DC / 80W DIM1 300 89 24 80	max.16 m	max.5 m (max.3m / Powerline)	max.3,6 m (max.3m / Powerline)	max.5,5 m		
LED POWER SUPPLY 24V-DC / 150W 300 89 24 150 OPTIONS 24V-DC / 5A DIM UNIT	max.30 m	max.10 m (max.3m / Powerline)	max.6,8 m (max.3m / Powerline)	max.10,4 m	⊗ max.18,72 m	
LED POWER SUPPLY MULTI POWER DIM7 300 90 60	max.4 m	max.1,3 m	max.0,9 m			
LED POWER SUPPLY MULTI POWER DIM6 300 90 61	max.4 m	max.1,3 m	max.0,9 m			
RGB DRIVER 12/24V-DC 75/150W 300 90 331				⊗ use in combination with Led Power Supply 24V-DC	⊗ use in combination with Led Power Supply 24V-DC	
TW TOUCH CONTROLLER DMX 300 90 332				⊗ use in combination with RGB Driver		
RGB TOUCH CONTROLLER DMX 300 90 330					⊗ use in combination with RGB Driver	

DIM1: dimming by 1-10V
 DIM6: dimming by push button / falling edge dimmer
 DIM7: dimming by push button / 1-10V

