




# ONE-AND-ONLY

PROFILE




**OAO - PROFILE** ◇  
**404 00 00** ◇  
 ◇ = B / GC / W  
 INCL.PC SBL HE  
 MAX.L / PROFILE: 5m  
 Kg / m

◇ [5,3]



TOL EN12020-2

END CAP



**OAO - END CAP SET** ◇  
**404 03 01** ◇  
 ◇ = B / W  
 SET OF 2 PCS

[0,4]

CORNER

FIXATION

**OAO - CABLE SUSPENSION SINGLE 1,6**  
**404 09 01**

L 1,6m

[0,1]

**OAO - CENTRAL ROD SUSPENSION 0,4m** ◇  
**328 27 40** ◇


◇ = B / W

[0,1]

**OAO - CENTRAL ROD SUSPENSION 0,8m** ◇  
**328 27 80** ◇

◇ = B / W

[0,1]



**CURRENT SUPPLY**

L 1,6m / 3 x 0,75mm<sup>2</sup> **377 98 51**

L 6,0m / 3 x 0,75mm<sup>2</sup> **377 98 56**


L 1,6m / 5 x 0,75mm<sup>2</sup> **377 99 51**

L 6,0m / 5 x 0,75mm<sup>2</sup> **377 99 56** [0,3]

**OPTIONS**

CABLE BASE R/S

COVERSET R 62-90-100 / S 62-80-90



**203 99 55** ◇

◇ = ANO / B / W

**203 99 56** ◇

◇ = ANO / B / W

[0,1]

**CURRENT SUPPLY**

**LED POWER SUPPLY 24V-DC KIT 60W DIM1**

**404 24 60 ED1**

220-240V / 50-60Hz


◇ CE [0,1] IP20

**LED POWER SUPPLY 24V-DC KIT 100W**


**404 24 100**

220-240V / 50-60Hz

◇ CE [0,1] IP20





<b>LEDFLEX</b> 5m - 24V-DC 0,3 
<b>WHITE</b>
Dividable per 55mm 126 smd LED/m
<b>10W/m</b> 1060lm/m *

CRI > 90

4000 K	IN	LEDFLEX IN MP 940 300 91 56 94
3000 K	IN	LEDFLEX IN MP 930 300 91 56 93
2700 K	IN	LEDFLEX IN MP 927 300 91 56 92

FULL INFO / PAG TEC

LED POWER SUPPLY 24V-DC / 20W 300 89 24 20 OPTIONS 24V-DC / 4A DIM UNIT	max.2m
LED POWER SUPPLY 24V-DC / 40W 300 89 24 40 OPTIONS 24V-DC / 4A DIM UNIT	max.4m
LED POWER SUPPLY 24V-DC / 60W 300 89 24 60 OPTIONS 24V-DC / 4A DIM UNIT	max.6m
LED POWER SUPPLY 24V-DC / 80W DIM1 300 89 24 80 ED1	max.8m
LED POWER SUPPLY 24V-DC / 150W 300 89 24 150 OPTIONS 24V-DC / 4A DIM UNIT	max.15m (max.10m / Powerline)
LED POWER SUPPLY MULTI POWER DIM7 300 90 60	max.2m
LED POWER SUPPLY MULTI POWER DIM6 300 90 61	max.2m

DIM1: dimming by 1-10V  
 DIM6: dimming by push button / falling edge dimmer  
 DIM7: dimming by push button / 1-10V

\*+/- 5%

FULL INFO TECHNICAL CHAPTER

**OPTIONS**

**CONTROL GEAR**

**24V-DC / 4A DIM1 UNIT** 90 x 22 x 17  
 300 90 003 ED1



**24V-DC / 4A DIM5 UNIT** 90 x 22 x 17  
 300 90 003 ED5



**24V-DC / 2 x 4A WIRELESS DIM UNIT** 90 x 22 x 17  
 300 90 010

