

BOXY 2 L+ 92733 DIM8



251 67 812 922 ED8 B-B

AVAILABLE IN

ALU GREY-ALU GREY 251 67 812 922 ED8 A-A

BLACK-BLACK 251 67 812 922 ED8 B-B

WHITE-WHITE 251 67 812 922 ED8 W-W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP53
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1201lm // 13,3W // 90lm/W

For detailed installation instructions, please consult the manual : [251 67 812_XXX_ED8_HAND.pdf](#)

DELTALIGHT

BOXY 2 L+ 92733 DIM8

251 67 812 922 ED8 B-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Light altering devices



Ø40



1.5

Ø45

251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



Ø40



1.5

Ø45

251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W



Ø40



1.5

Ø45

251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W

Notes: