



BOXY R OK 92733 DIM8

251 77 811 922 ED8 B-FG

AVAILABLE IN



BLACK-BLACK 251 77 811 922 ED8 B-B

BLACK-FLEMISH BRONZE 251 77 811 922 ED8 B-FBR

BLACK-FLEMISH GOLD 251 77 811 922 ED8 B-FG

WHITE-BLACK 251 77 811 922 ED8 W-B

WHITE-WHITE 251 77 811 922 ED8 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL CLASS	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	743lm // 9,9W // 75lm/W

For detailed installation instructions, please consult the manual : [251_77_811_XXX_HAND.pdf](#)


DELTALIGHT

BOXY R OK 92733 DIM8

251 77 811 922 ED8 B-FG

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: