



CARREE ST LED IP 92733

REFERENCE

11045 9220 W

AVAILABLE IN

WHITE 11045 9220 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.35
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	828lm // 9,9W // 84lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

Options

PLASTERKIT 161
CONCRETE BOX 161
MOUNTING KIT 75


For detailed installation instructions, please consult the manual : [11045_XXXX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	 202 00 75 - MOUNTING KIT 75 Required
 Stucanet	 202 00 75 - MOUNTING KIT 75 Required
	 207 01 161 - PLASTERKIT 161 Required
 Wood	-
 Concrete + plaster	 270 11 161 - CONCRETE BOX 161 Required
	 207 01 161 - PLASTERKIT 161 Required
 Lintel + plaster	 207 01 161 - PLASTERKIT 161 Required
	 270 11 161 - CONCRETE BOX 161 Required
 Hollow-core slab + plaster	 270 11 161 - CONCRETE BOX 161 Required
	 207 01 161 - PLASTERKIT 161 Required
 Stretched ceiling	-









FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐
Cutout dimension (mm): 27	
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐











CARREE ST LED IP 92733

11045 9220 W

LED power supplies		# of Fixtures
<div><div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		Min current Max current
<div><div></div><div><div>300 48 350 ED1</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 30</div></div></div>	1	☐
<div><div></div><div><div>300 48 350 ED5</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5</div><div>Dimtype: DALI</div><div>Cutout dimension (mm): 45</div></div></div>	1	☐
<div><div></div><div><div>300 48 350 MDL</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 30</div></div></div>	1	☐
<div><div></div><div><div>300 48 350 WDL</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL</div><div>Dimtype: WDL = wireless dimmable</div><div>Cutout dimension (mm): 45</div></div></div>	1	☐
<div><div></div><div><div>300 48 500 ED1</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 30</div></div></div>	1	☐
<div><div></div><div><div>300 48 500 ED5</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5</div><div>Dimtype: DALI</div><div>Cutout dimension (mm): 45</div></div></div>	1	☐
<div><div></div><div><div>300 48 500 MDL</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 30</div></div></div>	1	☐
<div><div></div><div><div>300 48 500 WDL</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL</div><div>Dimtype: WDL = wireless dimmable</div><div>Cutout dimension (mm): 45</div></div></div>	1	☐










CARREE ST LED IP 92733

11045 9220 W

	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	2(1) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	2	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	2->6(6) 6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	3(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	3->3 2->3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	3(3) 3(3)	☐

CARREE ST LED IP 92733

11045 9220 W


	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	3 3	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	2->3	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2 2	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

DELTALIGHT

CARREE ST LED IP 92733

11045 9220 W

Plasterkits




207 01 161 PLASTERKIT 161



Cutout dimension (mm): 175 x 175

Concrete boxes




270 11 161 CONCRETE BOX 161



Cutout dimension (mm): 207 x 207

Mounting kits



202 00 75 MOUNTING KIT 75



Cutout dimension (mm): 121

Notes: