


CEILING BASE 3L

23945 0010 B

AVAILABLE IN
BLACK 23945 0010 B



 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1

Electrical info

CLASS	I
CERTIFICATES	CB, EAC, ENEC

For detailed installation instructions, please consult the manual : [23945_0010_HAND.pdf](#)

WHERE USED

23910 0000	MILES C1 E27 PINK
23911 0000	MILES C1 E27 SMOKE
23912 0000	MILES C1 E27 MIST
23913 0000	MILES C1 E27 AMBER
23914 0000	MILES C2 E27 PINK
23915 0000	MILES C2 E27 SMOKE
23916 0000	MILES C2 E27 MIST
23917 0000	MILES C2 E27 AMBER
23918 0000	MILES C3 E27 PINK
23919 0000	MILES C3 E27 SMOKE
23920 0000	MILES C3 E27 MIST
23921 0000	MILES C3 E27 AMBER
23922 0000	MILES C4 E27 PINK
23923 0000	MILES C4 E27 SMOKE
23924 0000	MILES C4 E27 MIST
23925 0000	MILES C4 E27 AMBER
23926 9230	MILES C1 PINK 92750
23927 9230	MILES C1 SMOKE 92750
23928 9230	MILES C1 MIST 92750
23929 9230	MILES C1 AMBER 92750
23930 9230	MILES C2 PINK 92750
23931 9230	MILES C2 SMOKE 92750
23932 9230	MILES C2 MIST 92750
23933 9230	MILES C2 AMBER 92750
23934 9230	MILES C3 PINK 92750
23935 9230	MILES C3 SMOKE 92750
23936 9230	MILES C3 MIST 92750

DELTALIGHT

CEILING BASE 3L

23945 0010 B

23937 9230	MILES C3 AMBER 92750
23938 9230	MILES C4 PINK 92750
23939 9230	MILES C4 SMOKE 92750
23940 9230	MILES C4 MIST 92750
23941 9230	MILES C4 AMBER 92750

Notes: