



CONFORM P14 DOWN-UP 953067 DIM4



26511 7324 W-B

AVAILABLE IN

BLACK-BLACK 26511 7324 B-B

BLACK-FLEMISH GOLD 26511 7324 B-FG

WHITE-BLACK 26511 7324 W-B



 [View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Ceiling Suspended |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 4.2 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | 60 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 650mA-DC DOWN / 500mA-DC UP 2 DALI CONTROL CHANNELS INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² NATURAL LIGHT TECHNOLOGY |

Electrical info

| | |
|---------------------|----------------------------|
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI or DSI or push button |
| ENERGY CLASS | D |
| CERTIFICATES | CB, ENEC, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN: LED cluster 22W / CRI>95 (R9: 80) / 3000K / 2568lm UP: LED cluster 16,8W / CRI>95 (R9: 80) / 3000K / 1978lm |
| TM-30 VALUES | Rf: 94 / Rg: 103 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 60000 |
| BEAMANGLE | 67° |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 2568lm // 22W // 117lm/W UP: 1978lm // 16,8W // 117lm/W |
| LED TECHNICS (LUMINAIRE) | DOWN: 1613lm // 25,3W // 64lm/W UP: 1559lm // 19,3W // 81lm/W |

Options

- CABLE BASE R / S
- COVERSET R 62-90-100 / S 62-80-90
- CONNECTION ST / CONNECTION TRIMLESS
- SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT

CONFORM P14 DOWN-UP 953067 DIM4

26511 7324 W-B

For detailed installation instructions, please consult the manual : [26511_XXX4_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W

Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

DELTALIGHT

CONFORM P14 DOWN-UP 953067 DIM4

26511 7324 W-B

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B

204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B


204 90 90 W COVERSET S 90 W

DELTALIGHT

CONFORM P14 DOWN-UP 953067 DIM4


26511 7324 W-B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: