



FRAX S 93047 HONEYCOMB



26001 9390 A

AVAILABLE IN

ALU GREY 26001 9390 A

FLEMISH BRONZE OUTDOOR 26001 9390 FBRX

ANTHRACITE 26001 9390 N



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.5
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	4 x LENS SP-14° INCLLED POWER SUPPLY 700mA-DC INCL.BEAM LENS 47° INCL.HONEYCOMB

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 8W / CRI>90 (R9: 60) / 3000K / 96lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	47°
LED TECHNICS (LIGHT SOURCE)	96lm // 8W // 120lm/W
LED TECHNICS (LUMINAIRE)	490lm // 9,2W // 53lm/W

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX S KAP

DELTALIGHT


FRAX S 93047 HONEYCOMB

26001 9390 A

For detailed installation instructions, please consult the manual : [26001_XX90_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



26070 0010 N FRAX S KAP N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

Notes: