
DELTALIGHT




HALOSCAN ON 1 MP 92721 DIM8

REFERENCE 23147 9228 W-W

AVAILABLE IN
BLACK-BLACK 23147 9228 B-B
BLACK-GOLD COLORED 23147 9228 B-GC
WHITE-WHITE 23147 9228 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-21° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	812lm // 9,9W // 82lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : **23147_XXX8_HAND.pdf**


DELTALIGHT

HALOSCAN ON 1 MP 92721 DIM8


23147 9228 W-W

FINISH YOUR SPECIFICATION


Light altering devices



23110 0040 HALOSCAN LINEAR SPREAD LENS ☐



23110 0050 B HALOSCAN HONEYCOMB B ☐



23110 0060 B HALOSCAN KAP MP B ☐

23110 0060 W HALOSCAN KAP MP W ☐

Notes: