



## HALOSCAN ON 1 MP 93014 DIM8



23147 9318 W-W

AVAILABLE IN

**BLACK-BLACK** 23147 9318 B-B

**BLACK-GOLD COLORED** 23147 9318 B-GC

**WHITE-WHITE** 23147 9318 W-W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	14°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	930lm // 9,9W // 94lm/W

### Accessories

HALOSCAN HONEYCOMB  
HALOSCAN LINEAR SPREAD LENS  
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23147\\_XXX8\\_HAND.pdf](#)

# DELTALIGHT


## HALOSCAN ON 1 MP 93014 DIM8

23147 9318 W-W

### FINISH YOUR SPECIFICATION


#### Light altering devices

---




**23110 0040**

HALOSCAN LINEAR SPREAD LENS



**23110 0050 B**

HALOSCAN HONEYCOMB B



**23110 0060 B**

HALOSCAN KAP MP B

**23110 0060 W**

HALOSCAN KAP MP W

Notes: