

HEAD ON 2 93033 DIMI

473 231 812 932 ED1 BBR-B



AVAILABLE IN

BLACK-BLACK 473 231 812 932 ED1 B-B

BLACK BRONZE-BLACK 473 231 812 932 ED1 BBR-B

GOLD COLORED-BLACK 473 231 812 932 ED1 GC-B

WHITE-WHITE 473 231 812 932 ED1 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1574lm // 11,6W // 135lm/W
LED TECHNICS (LUMINAIRE)	790lm // 13,3W // 59lm/W

Requirements

VIZIR TUBE

Accessories

VIZIR HONEYCOMB

VIZIR SOFTENING LENS

For detailed installation instructions, please consult the manual : [473 231 812 XXX ED1 HAND.pdf](#)


DELTALIGHT

HEDRA ON 2 93033 DIM1

473 231 812 932 ED1 BBR-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 016 ED1 WIRELESS CONTROL 5A DIM1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

Light altering devices




473 03 01 B VIZIR HONEYCOMB B



473 03 04 VIZIR SOFTENING LENS

Finish your product



473 01 00 B VIZIR TUBE B

473 01 00 FBR VIZIR TUBE FBR

473 01 00 FG VIZIR TUBE FG

473 01 00 W VIZIR TUBE W

Notes: