



## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W

AVAILABLE IN  
**BLACK** 24210 9230 B  
**WHITE** 24210 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 98
<b>RECESSED DEPTH (MM)</b>	125
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	max.25
<b>INGRESS PROTECTION</b>	IP20 or IP54 (with TUBE IP)
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	0° to 30° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	974lm // 8,6W // 113lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	762lm // 9,9W // 77lm/W

### Requirements

iMAX II TUBE ROUND  
LED POWER SUPPLY 350 / 500mA-DC DIM

### Accessories

iMAX II ACCESSOIRES

For detailed installation instructions, please consult the manual : [24210\\_XXXX\\_HAND.pdf](#)



# DELTALIGHT

## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W



**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

**Dimtype: non-dimmable**

**Cutout dimension (mm): 30**



**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 45**



**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

**Dimtype: 1-10V**

**Cutout dimension (mm): 30**



**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

**Dimtype: DALI**

**Cutout dimension (mm): 45**



**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

**Dimtype: non-dimmable**

**Cutout dimension (mm): 30**




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 45**




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

**Dimtype: mains (phase cut-off) or push button**

**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 82**



**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | -

**Dimtype: 1-10V or DALI or push button**

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 72




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 55




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4



Dimtype: non-dimmable

Cutout dimension (mm): 90




**21012 0010** LED POWER SUPPLY MULTI POWER

2 | 2



Dimtype: non-dimmable

Cutout dimension (mm): 50




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

3 | 3



Dimtype: 1-10V

Cutout dimension (mm): 54




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

3 | 3



Dimtype: DALI

Cutout dimension (mm): 54




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

4(4) | 4(3)



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0308** LED POWER SUPPLY 350mA / 7,35W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0318** LED POWER SUPPLY 500mA / 10W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**



**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2


**Dimtype: DALI**

**Cutout dimension (mm): 30**

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W



**21032 0305**

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30

### Mounting kits




**15215 0010** MOUNTING KIT FLUSH iMAX II ROUND




Cutout dimension (mm): 121

### Light altering devices



**24213 0050 B** iMAX II HONEYCOMB B



**24213 0060** iMAX II GLASS SBL



**24213 0070** iMAX II LINEAR SPREAD LENS



**24213 0090** iMAX II SOFTENING LENS



**24213 0100** iMAX II SPREAD LENS



# DELTALIGHT

## iMAX II ROUND ADJUSTABLE LP 92733

24210 9230 W

### Finish your product

---



**24213 0010 B**

iMAX II TUBE ROUND B

**24213 0010 FG**


iMAX II TUBE ROUND FG

**24213 0010 MMAT**

iMAX II TUBE ROUND MMAT

**24213 0010 W**

iMAX II TUBE ROUND W



**24213 0040 B**

iMAX II TUBE ROUND IP B

**24213 0040 FG**

iMAX II TUBE ROUND IP FG

**24213 0040 MMAT**

iMAX II TUBE ROUND IP MMAT

**24213 0040 W**

iMAX II TUBE ROUND IP W

Notes: