



## iMAX II ROUND ADJUSTABLE MP 92739

24211 9230 B

AVAILABLE IN  
**BLACK** 24211 9230 B  
**WHITE** 24211 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 98
<b>RECESSED DEPTH (MM)</b>	155
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	max.25
<b>INGRESS PROTECTION</b>	IP20 or IP54 (with TUBE IP)
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	0° to 30° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS FL-39° EXCL.LED POWER SUPPLY 350-500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	39°
<b>LED TECHNICS (LIGHT SOURCE)</b>	2009lm // 17,2W // 117lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1352lm // 19,8W // 68lm/W

### Remarks

No HONEYCOMB, SPREAD LENS or LINEAR SPREAD LENS @ 500mA !  
 No accessories with iMAX II TUBE ROUND IP !

### Requirements

iMAX II TUBE ROUND  
 LED POWER SUPPLY 350 / 500mA-DC DIM

### Accessories

iMAX II ACCESSOIRES



# DELTALIGHT

## iMAX II ROUND ADJUSTABLE MP 92739

24211 9230 B



**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30



**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

1 | 1

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

2(2) | 2(2)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(0)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE MP 92739

24211 9230 B




**300 90 67**

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

1 | -

**Dimtype: 1-10V or DALI or push button**




**300 90 68**

LED POWER SUPPLY MULTI-POWER DIM5

1(1) | 1(0)

**Dimtype: DALI**

**Cutout dimension (mm): 72**




**300 90 69**

LED POWER SUPPLY MULTI-POWER HV DIM9

3(3) | 3(2)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124**

LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(0)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125**

LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1) | 1(0)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135**

LED POWER SUPPLY MULTI-POWER HV

2->2 | 2

**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**21012 0010**

LED POWER SUPPLY MULTI POWER

1 | 1

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021**

LED POWER SUPPLY MULTI POWER DIM1

1 | 1

**Dimtype: 1-10V**

**Cutout dimension (mm): 54**




**21012 0035**

LED POWER SUPPLY MULTI POWER DIM5

1 | 1

**Dimtype: DALI**

**Cutout dimension (mm): 54**



**21012 004W**

LED POWER SUPPLY MULTI-POWER WDL

2(2) | 2(2)

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE MP 92739

24211 9230 B




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

1|1

**Dimtype:** WDL = wireless dimmable

**Cutout dimension (mm):** 54




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 50




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 55




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1|1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 48




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

1(1)

**Dimtype:** non-dimmable

**Cutout dimension (mm):** 60




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

1(0)

**Dimtype:** non-dimmable

**Cutout dimension (mm):** 60



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

**Dimtype:** DALI

**Cutout dimension (mm):** 30




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

**Dimtype:** DALI

**Cutout dimension (mm):** 30

### Mounting kits



**15215 0010** MOUNTING KIT FLUSH iMAX II ROUND

**Cutout dimension (mm):** 121


# DELTALIGHT

## iMAX II ROUND ADJUSTABLE MP 92739


24211 9230 B

### Light altering devices


---



**24213 0050 B** iMAX II HONEYCOMB B




**24213 0060** iMAX II GLASS SBL



**24213 0070** iMAX II LINEAR SPREAD LENS




**24213 0090** iMAX II SOFTENING LENS



**24213 0100** iMAX II SPREAD LENS

### Finish your product

---




**24213 0010 B** iMAX II TUBE ROUND B

**24213 0010 FG** iMAX II TUBE ROUND FG

**24213 0010 MMAT** iMAX II TUBE ROUND MMAT

**24213 0010 W** iMAX II TUBE ROUND W



**24213 0040 B** iMAX II TUBE ROUND IP B

# DELTALIGHT

## iMAX II ROUND ADJUSTABLE MP 92739

24211 9230 B

---

**24213 0040 FG** iMAX II TUBE ROUND IP FG

---

**24213 0040 MMAT** iMAX II TUBE ROUND IP MMAT

---

**24213 0040 W** iMAX II TUBE ROUND IP W

Notes: