





iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W

AVAILABLE IN
BLACK 24211 9310 B
WHITE 24211 9310 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 98
RECESSED DEPTH (MM)	155
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20 or IP54 (with TUBE IP)
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS SP-18° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 52) / 3000K / 1524-2101lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2101lm // 17,2W // 123lm/W
LED TECHNICS (LUMINAIRE)	1450lm // 19,8W // 73lm/W

Requirements

iMAX II TUBE ROUND
 LED POWER SUPPLY 350 / 500mA-DC DIM

Accessories

iMAX II ACCESSOIRES

For detailed installation instructions, please consult the manual : [24211_XXXX_HAND.pdf](#)

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

1 | 1

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

2(2) | 2(2)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(0)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

1 | -

Dimtype: 1-10V or DALI or push button

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(1) | 1(0)

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

3(3) | 3(2)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(0)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1) | 1(0)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 135 LED POWER SUPPLY MULTI-POWER HV

2->2 | 2

Dimtype: non-dimmable

Cutout dimension (mm): 90




21012 0010 LED POWER SUPPLY MULTI POWER

1 | 1

Dimtype: non-dimmable

Cutout dimension (mm): 50




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

1 | 1

Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5

1 | 1

Dimtype: DALI

Cutout dimension (mm): 54




21012 004W LED POWER SUPPLY MULTI-POWER WDL

2(2) | 2(2)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1 | 1


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1|1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 30




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 30

Mounting kits



15215 0010 MOUNTING KIT FLUSH iMAX II ROUND


Cutout dimension (mm): 121

DELTALIGHT


iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W


Light altering devices



24213 0050 B iMAX II HONEYCOMB B




24213 0060 iMAX II GLASS SBL



24213 0070 iMAX II LINEAR SPREAD LENS




24213 0090 iMAX II SOFTENING LENS



24213 0100 iMAX II SPREAD LENS

Finish your product




24213 0010 B iMAX II TUBE ROUND B

24213 0010 FG iMAX II TUBE ROUND FG

24213 0010 MMAT iMAX II TUBE ROUND MMAT

24213 0010 W iMAX II TUBE ROUND W



24213 0040 B iMAX II TUBE ROUND IP B

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 93018

24211 9310 W

24213 0040 FG iMAX II TUBE ROUND IP FG

24213 0040 MMAT iMAX II TUBE ROUND IP MMAT

24213 0040 W iMAX II TUBE ROUND IP W

Notes: