

INFORM RI+ CS DOWN-UP 92748 DIM5

26816 9225 B-B

AVAILABLE IN



BLACK-BLACK 26816 9225 B-B

BLACK-FLEMISH GOLD 26816 9225 B-FG

FLEMISH GOLD-BLACK 26816 9225 FG-B

WHITE-BLACK 26816 9225 W-B

WHITE-WHITE 26816 9225 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 700mA-DC 2 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2761lm // 26,3W // 105lm/W UP: 1106lm // 13,2W // 84lm/W

For detailed installation instructions, please consult the manual : [26816_XXX5_HAND.pdf](#)

DELTALIGHT

INFORM R1+ CS DOWN-UP 92748 DIM5

26816 9225 B-B

Notes: