DELTALIGHT

INFORM R1+ CS DOWN-UP 93048 DIM5

26816 9325 B-B

AVAILABLE IN
BLACK-BLACK 26816 9325 B-B
BLACK-FLEMISH GOLD 26816 9325 B-FG
FLEMISH GOLD-BLACK 26816 9325 FG-B
WHITE-BLACK 26816 9325 W-B
WHITE-WHITE 26816 9325 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 700mA-DC 2 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 3000K / 1752lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3504lm // 22,9W // 153lm/W UP: 1752lm // 11,5W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2800lm // 26,3W // 106lm/W UP: 1121lm // 13,2W // 85lm/W

For detailed installation instructions, please consult the manual : **26816_XXX5_HAND.pdf**

INFORM R1+ CS DOWN-UP 93048 DIM5

26816 9325 B-B

Notes: