



## INFORM RI DOWN-UP 92748

26812 9220 W-B

AVAILABLE IN



**BLACK-BLACK** 26812 9220 B-B

**BLACK-FLEMISH GOLD** 26812 9220 B-FG

**FLEMISH GOLD-BLACK** 26812 9220 FG-B

**WHITE-BLACK** 26812 9220 W-B

**WHITE-WHITE** 26812 9220 W-W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	2.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	96 x REFLECTOR WFL-71° (DOWN) EXCL. 2 x POWER SUPPLY 700mA-DC (DOWN/UP) INCL. 4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL. 1 x CABLE 5 x 0.75mm <sup>2</sup>

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	C
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
<b>SDCM</b>	SDCM3
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	71°
<b>LED TECHNICS (LIGHT SOURCE)</b>	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	DOWN: 2761lm // 26,3W // 105lm/W UP: 1106lm // 13,2W // 84lm/W

### Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)

### Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

# DELTALIGHT


## INFORM R1 DOWN-UP 92748

26812 9220 W-B

For detailed installation instructions, please consult the manual : [26812\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W



**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

1 down | 1 up

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

1 down | 1 up

**Dimtype: DALI**


**Cutout dimension (mm): 72**

# DELTALIGHT

## INFORM R1 DOWN-UP 92748

26812 9220 W-B


### Coversets



**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B


**204 00 62 W** COVERSET R 62 W



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B


**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B

**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO


**204 80 80 B** COVERSET S 80 B

# DELTALIGHT

## INFORM R1 DOWN-UP 92748

26812 9220 W-B

**204 80 80 W** COVERSET S 80 W




**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B


**204 90 90 W** COVERSET S 90 W

### Suspension parts



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




**15225 0340 B** SUSPENSION ST B

Cutout dimension (mm): 27

**15225 0340 W** SUSPENSION ST W

### Electric connection parts



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43

**15225 0360 W** CONNECTION ST W

# DELTALIGHT

## **INFORM R1 DOWN-UP 92748**

26812 9220 W-B

Notes: