



INFORM R2 DOWN-UP 93048

26818 9320 B-B

AVAILABLE IN



BLACK-BLACK 26818 9320 B-B

BLACK-FLEMISH GOLD 26818 9320 B-FG

FLEMISH GOLD-BLACK 26818 9320 FG-B

WHITE-BLACK 26818 9320 W-B

WHITE-WHITE 26818 9320 W-W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) EXCL. 2 x POWER SUPPLY 700mA-DC (DOWN/UP) INCL. 4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL. 1 x CABLE 5 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 3000K / 1752lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3504lm // 22,9W // 153lm/W UP: 1752lm // 11,5W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2800lm // 26,3W // 106lm/W UP: 1121lm // 13,2W // 85lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM R2 DOWN-UP 93048

26818 9320 B-B

For detailed installation instructions, please consult the manual : [26818_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1 down | 1 up

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1 down | 1 up

Dimtype: DALI


Cutout dimension (mm): 72

DELTALIGHT

INFORM R2 DOWN-UP 93048

26818 9320 B-B


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B


204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B


204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B

204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO


204 80 80 B COVERSET S 80 B

DELTALIGHT

INFORM R2 DOWN-UP 93048

26818 9320 B-B

204 80 80 W COVERSET S 80 W




204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B


204 90 90 W COVERSET S 90 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

DELTALIGHT

INFORM R2 DOWN-UP 93048

26818 9320 B-B

Notes: