



INFORM R3+ DOWN 92748 DIM5

26821 9225 W-B

AVAILABLE IN



BLACK-BLACK 26821 9225 B-B

BLACK-FLEMISH GOLD 26821 9225 B-FG

FLEMISH GOLD-BLACK 26821 9225 FG-B

WHITE-BLACK 26821 9225 W-B

WHITE-WHITE 26821 9225 W-W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.2
ADJUSTABILITY	non adjustable
INFORMATION	168 x REFLECTOR WFL-71° INCL.DIMMABLE LED POWER SUPPLY 1050mA-DC

Electrical info

ELECTRICAL CLASS	220-240V / 0 50-60Hz
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 33,9W / CRI>90 (R9: 50) / 2700K / 5208lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	5208lm // 33,9W // 153lm/W
LED TECHNICS (LUMINAIRE)	4349lm // 39W // 112lm/W

Options

SUSPENSION SET 32 5x0,75 1,6m
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : [26821_XXX5_HAND.pdf](#)


DELTALIGHT

INFORM R3+ DOWN 92748 DIM5

26821 9225 W-B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W



203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W

DELTALIGHT

INFORM R3+ DOWN 92748 DIM5


26821 9225 W-B



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B


204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B


204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B

204 90 90 W COVERSET S 90 W

Suspension parts



15225 0320 B SUSPENSION SET 32 5x0,75 1,6m B

DELTALIGHT

INFORM R3+ DOWN 92748 DIM5

26821 9225 W-B

15225 0320 W SUSPENSION SET 32 5x0,75 1,6m W



Electric connection parts



15225 0360 B CONNECTION ST B



Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W



Notes: