





INLET S WW

304 05 12 W

AVAILABLE IN
ALU GREY 304 05 12 A
WHITE 304 05 12 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 22 x 170
RECESSED DEPTH (MM)	45
THICKNESS OF MOUNTING SURFACE (MM)	min.12
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 1W / CRI>80 (R9: 6) / 3000K / 132lm
TM-30 VALUES	rf: 86 / Rg: 95
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	132lm // 1W // 132lm/W
LED TECHNICS (LUMINAIRE)	16lm // 1,2W // 14lm/W

Requirements	
LED POWER SUPPLY 350mA-DC DIM	

Options	
PLASTERKIT 145	
CONCRETE BOX 145	
MOUNTING KIT FLUSH INLET	

For detailed installation instructions, please consult the manual : [304_05_12_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3->14

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3->14

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3->14

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3->14

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

3->11

Dimtype: 1-10V

Cutout dimension (mm): 30




300 90 60 LED POWER SUPPLY MULTI-POWER DIM7

11(11) | - | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 70




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

16

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

26(25)











Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82

DELTALIGHT

INLET S WW









304 05 12 W

	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	4->18(15)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	3->15	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2->17(15)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	8->40(39)	☐
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non-dimmable Cutout dimension (mm): 40	14(10)	☐
	300 90 104 LED POWER SUPPLY 350mA-DC / 6W	4	☐
	300 90 108 LED POWER SUPPLY 350mA-DC / 8W Dimtype: non-dimmable Cutout dimension (mm): 40	6(6)	☐
	300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 42	5->10	☐
	300 90 112 LED POWER SUPPLY 350mA-DC / 18W Dimtype: mains (phase cut-off)	15	☐
	300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	10->18 - -	☐

DELTALIGHT

INLET S WW







304 05 12 W

	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	6->17(15)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	4->17(15)	☐
	300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 84	4->31(31) - -	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	17->29	☐
	300 90 913 LED POWER SUPPLY 350mA-DC / 17W Dimtype: non-dimmable Cutout dimension (mm): 46	13(9)	☐
	300 90 914 LED POWER SUPPLY MULTI-POWER Dimtype: non-dimmable Cutout dimension (mm): 82	19(19) - -	☐
	300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 43	7->12(12)	☐
	300 2415 350 LED POWER CONVERTER 24V-DC TO 350mA / 15W	3->12	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	6->15	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	4->19	☐

DELTALIGHT

INLET S WW

304 05 12 W

	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	4->19	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	25(25)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	4->19	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	7->10	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	10->15	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	3->15	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	5->7	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2->17(15)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	3->15	☐

DELTALIGHT

INLET S WW

304 05 12 W

Plasterkits




304 05 99 PLASTERKIT 145



Cutout dimension (mm): 110 x 180

Concrete boxes




304 05 98 CONCRETE BOX 145



Cutout dimension (mm): 155 x 215

Mounting kits



304 05 01 MOUNTING KIT FLUSH INLET S



Cutout dimension (mm): 55 x 190

Notes: