



## LASS-OH! L330-6 93034

24819 9320 GC

AVAILABLE IN  
**BLACK** 24819 9320 B  
**GOLD COLOURED** 24819 9320 GC



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.4
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.6 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm <sup>2</sup>

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	6 x (LED cluster 6,1W / CRI>90 (R9: 50) / 3000K / 683lm)
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	34°
<b>LED TECHNICS (LIGHT SOURCE)</b>	4098lm // 36,6W // 112lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	3239lm // 42,1W // 77lm/W

### Requirements

LASS-OH! POWERBOX  
LED POWER SUPPLY 1050mA-DC DIM

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

### Accessories

JIHA S / R

# DELTALIGHT


## LASS-OH! L330-6 93034

24819 9320 GC

For detailed installation instructions, please consult the manual : [24819\\_XXXX\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W



**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21012 0010** LED POWER SUPPLY MULTI POWER

1

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**



**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

1


**Dimtype: 1-10V**

**Cutout dimension (mm): 54**

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 GC



**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

1

Dimtype: DALI

Cutout dimension (mm): 54


### Power box

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**24814 0010 B** LASS-OH! POWERBOX B

1


Dimtype: non-dimmable



**24814 0011 B** LASS-OH! POWERBOX DIM1 B

1

Dimtype: 1-10V




**24814 0015 B** LASS-OH! POWERBOX DIM5 B

1

Dimtype: DALI


### Coversets



**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W



**204 00 90 ANO** COVERSET R 90 ANO


**204 00 90 B** COVERSET R 90 B

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 GC


**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B


**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO

**204 80 80 B** COVERSET S 80 B

**204 80 80 W** COVERSET S 80 W



**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B

**204 90 90 W** COVERSET S 90 W

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 GC

### Suspension parts

---



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



**15225 0340 B** SUSPENSION ST B

Cutout dimension (mm): 27

**15225 0340 W** SUSPENSION ST W

### Electric connection parts

---



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43


**15225 0360 W** CONNECTION ST W

### Light altering devices

---



**24814 0020 B** JIHA! S B



**24814 0030 B** JIHA! R B

# DELTALIGHT

## **LASS-OH! L330-6 93034**

24819 9320 GC

Notes: