




LOGIC F2

213 47 122 A

AVAILABLE IN
ALU GREY 213 47 122 A



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC max.600kg

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED 0,6W / CRI>80 / 3000K / 45lm)
LED TECHNICS (LIGHT SOURCE)	90lm // 1,2W // 75lm/W
LED TECHNICS (LUMINAIRE)	7lm // 1,4W // 5lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

GENIE BOX 90 R
CBOX

For detailed installation instructions, please consult the manual : [213_47_112_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 24 20

LED POWER SUPPLY 24V-DC / 20W

16

Dimtype: non-dimmable

Cutout dimension (mm): 60




300 89 24 40

LED POWER SUPPLY 24V-DC / 40W

33

Dimtype: non-dimmable

Cutout dimension (mm): 55




300 89 24 60

LED POWER SUPPLY 24V-DC / 60W

50

Dimtype: non-dimmable

Cutout dimension (mm): 55




300 89 24 61

LED POWER SUPPLY 24V-DC / 60W DIN

50

Dimtype: non-dimmable




300 89 24 80 ED1

LED POWER SUPPLY 24V-DC / 80W DIM1

66

Dimtype: 1-10V

Cutout dimension (mm): 75




300 89 24 150

LED POWER SUPPLY 24V-DC / 150W

125

Dimtype: non-dimmable

Cutout dimension (mm): 75



21012 0160

LED POWER SUPPLY 24V-DC / 24W

20

Dimtype: non-dimmable


Cutout dimension (mm): 55

DELTALIGHT

LOGIC F2

213 47 122 A

Ground mounting boxes




213 19 09 LOGIC 90 BOX R



Cutout dimension (mm): 224 x 159

Waterproof connection parts



216 12 00 CBOX



Cutout dimension (mm): 142 x 142

Notes: