



MICROSPY IN 93030

24110 9320 B

AVAILABLE IN
BLACK 24110 9320 B
WHITE 24110 9320 W



 [View on website](#)



General info

| | |
|---|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Recessed |
| CUTOUT SHAPE/SIZE (MM) | round - 36 |
| RECESSED DEPTH (MM) | 75 |
| THICKNESS OF MOUNTING SURFACE (MM) | min.2 - max.25 |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.1 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | LENS FL-30° EXCL.LED POWER SUPPLY 350-450mA-DC |

Electrical info

| | |
|---------------------|---------------------------|
| CLASS | III |
| DIM TYPE | depending on power supply |
| ENERGY CLASS | F |
| CERTIFICATES | CB, EAC, ENEC |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 3,9-5,1W / CRI>90 (R9: 55) / 3000K / 385-480lm |
| TM-30 VALUES | rf: 92 / Rg: 98 |
| SDCM | SDCM2 |
| RISKGROUP | RG2 (threshold 0,6m) |
| LM80 | L90B10 > 41000 |
| BEAMANGLE | 30° |
| LED TECHNICS (LIGHT SOURCE) | 480lm // 5,1W // 94lm/W |
| LED TECHNICS (LUMINAIRE) | 376lm // 5,9W // 64lm/W |

Requirements

LED POWER SUPPLY 350 / 450mA-DC DIM










For detailed installation instructions, please consult the manual : [24110_XXXX_HAND.pdf](#)

DELTALIGHT

MICROSPY IN 93030

24110 9320 B

CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|--------------|
|  System ceiling | - |
|  Plasterboard | - |
|  Stucanet | - |
|  Wood | - |
|  Concrete | - |
|  Concrete + plaster | - |
|  Lintel + plaster | - |
|  Hollow-core slab + plaster | - |
|  Stretched ceiling | - |

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45

DELTALIGHT

MICROSPY IN 93030

24110 9320 B



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

3 | - | -

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

6(6) | -

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

4(3) | - | -

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3 | - | -

Dimtype: 1-10V or DALI or push button




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

3(3) | - | -

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 2->9(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 91 LED POWER SUPPLY 350mA-DC / 15W

3(2)

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 108 LED POWER SUPPLY 350mA-DC / 8W

1


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

MICROSPY IN 93030

24110 9320 B




300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42




300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8

3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7

2->8(8) | - | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 84




300 90 135 LED POWER SUPPLY MULTI-POWER HV

4->6 | - | -

Dimtype: non-dimmable

Cutout dimension (mm): 90




300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 43




21012 004W LED POWER SUPPLY MULTI-POWER WDL

5(5) | - | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48

DELTALIGHT

MICROSPY IN 93030

24110 9320 B




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)



Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3



Dimtype: DALI

Cutout dimension (mm): 30

Notes: