





NEEDLE 1 TRC OK 92713

25015 9210 BBR

AVAILABLE IN
BLACK BRONZE 25015 9210 BBR
FLEMISH GOLD 25015 9210 FG



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 50° swiveling, 350° rotatable
INFORMATION	LENS SP-13° EXCL.LED POWER SUPPLY 350-500mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-5,7W / CRI>90 (R9: 56) / 2700K / 385-519lm
TM-30 VALUES	rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	13°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,7W // 90lm/W
LED TECHNICS (LUMINAIRE)	364lm // 6,6W // 56lm/W
Requirements	
CONNECTION TRIMLESS	
LED POWER SUPPLY 350 / 500mA-DC DIM	

For detailed installation instructions, please consult the manual : [25015_XXXX_HAND.pdf](#)

DELTALIGHT

NEEDLE 1 TRC OK 92713

25015 9210 BBR

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

NEEDLE 1 TRC OK 92713

25015 9210 BBR



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

3 | 3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

6(6) | 6(6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 4(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3

Dimtype: 1-10V or DALI or push button




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

4(3) | 4(2)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 9(6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 92 LED POWER SUPPLY 500mA-DC / 21W

3(1)

Dimtype: non-dimmable

Cutout dimension (mm): 48




300 90 108 LED POWER SUPPLY 350mA-DC / 8W

1

Dimtype: non-dimmable

Cutout dimension (mm): 40




300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8

3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



300 90 119 LED POWER SUPPLY 500mA-DC / 11W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42

DELTALIGHT

NEEDLE 1 TRC OK 92713

25015 9210 BBR



300 90 121 LED POWER SUPPLY 500mA-DC / 20W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7

2->8(8) | 8(6) | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 84




300 90 135 LED POWER SUPPLY MULTI-POWER HV

5->7 | 4->7 | 4->6

Dimtype: non-dimmable

Cutout dimension (mm): 90




300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 43




300 90 5120 LED POWER SUPPLY 500mA-DC / 22W DIM8

3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 61




21012 0010 LED POWER SUPPLY MULTI POWER

2->3 | 3

Dimtype: non-dimmable

Cutout dimension (mm): 50




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

4 | 4

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5

4 | 4


Dimtype: DALI

Cutout dimension (mm): 54

DELTALIGHT

NEEDLE 1 TRC OK 92713

25015 9210 BBR




21012 004W LED POWER SUPPLY MULTI-POWER WDL

6(6) | 5(5)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | 4 | 4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

4->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3 | 3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

4(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3


Dimtype: DALI

Cutout dimension (mm): 30

DELTALIGHT

NEEDLE 1 TRC OK 92713

25015 9210 BBR



21032 0305

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5


3



Dimtype: DALI

Cutout dimension (mm): 30

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.



Cutout dimension (mm): 62 (CONCRETE: 102)

Notes: