



PARTOU S IP 92725

25216 9220 B



AVAILABLE IN

BLACK 25216 9220 B

FLEMISH BRONZE 25216 9220 FBR

FLEMISH GOLD 25216 9220 FG

WHITE 25216 9220 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-25° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	748lm // 9,9W // 76lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

For detailed installation instructions, please consult the manual : [25216_XXX0_HAND.pdf](#)

DELTALIGHT

PARTOU S IP 92725

25216 9220 B

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

PARTOU S IP 92725

25216 9220 B



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | -

Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 91 LED POWER SUPPLY 350mA-DC / 15W

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4











Dimtype: non-dimmable

Cutout dimension (mm): 90

DELTALIGHT

PARTOU S IP 92725


25216 9220 B

	21012 0010 LED POWER SUPPLY MULTI POWER	2 2 <input type="checkbox"/>
	Dimtype: non-dimmable	
	Cutout dimension (mm): 50	
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	3 3 <input type="checkbox"/>
	Dimtype: 1-10V	
	Cutout dimension (mm): 54	
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	3 3 <input type="checkbox"/>
	Dimtype: DALI	
	Cutout dimension (mm): 54	
	21012 004W LED POWER SUPPLY MULTI-POWER WDL	4(4) 4(3) <input type="checkbox"/>
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 84	
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 3 <input type="checkbox"/>
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 54	
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1 <input type="checkbox"/>
	Dimtype: mains (phase cut-off)	
	Cutout dimension (mm): 50	
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 <input type="checkbox"/>
	Dimtype: mains (phase cut-off)	
	Cutout dimension (mm): 50	
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 <input type="checkbox"/>
	Dimtype: mains (phase cut-off)	
	Cutout dimension (mm): 55	
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->3 <input type="checkbox"/>
	Dimtype: mains (phase cut-off)	
	Cutout dimension (mm): 55	
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 2 <input type="checkbox"/>
	Dimtype: mains (phase cut-off)	
	Cutout dimension (mm): 48	

DELTALIGHT

PARTOU S IP 92725

25216 9220 B




21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 30

Notes: