





PUNK 452 C 93040 DIM8

471 222 932 ED8 GC

AVAILABLE IN

BLACK 471 222 932 ED8 B

GOLD COLOURED 471 222 932 ED8 GC



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7,4W // 66lm/W

Requirements

MIDISPY TUBE

Options

SUSPENSION + CONNECTION TRIMLESS

COVERSET R 90-100

For detailed installation instructions, please consult the manual : [471 222_XXX_ED8_HAND.pdf](#)

PUNK 452 C 93040 DIM8

471 222 932 ED8 GC

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40


Coversets



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W




204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.


Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT

PUNK 452 C 93040 DIM8

471 222 932 ED8 GC

Finish your product



414 03 00 B

MIDISPY TUBE B

414 03 00 FBR

MIDISPY TUBE FBR

414 03 00 FG

MIDISPY TUBE FG

414 03 00 MMAT

MIDISPY TUBE MMAT

414 03 00 SG

MIDISPY TUBE SG

414 03 00 W

MIDISPY TUBE W

Notes: