





PUNK 622 C 93033 DIM8

471 322 811 932 ED8 B

AVAILABLE IN

BLACK 471 322 811 932 ED8 B

GOLD COLOURED 471 322 811 932 ED8 GC



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	404lm // 6,7W // 61lm/W

Requirements

SPY TUBE

Options

SUSPENSION + CONNECTION TRIMLESS

COVERSET R 90-100

Accessories

HONEYCOMB 50

LINEAR SPREAD LENS 50

SPREAD LENS 50

SOFTENING LENS 50

DELTALIGHT

PUNK 622 C 93033 DIM8


471 322 811 932 ED8 B

GLASS SBL 50

For detailed installation instructions, please consult the manual : [471_322_811_XXX_ED8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40


Coversets



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W




204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.


Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT


PUNK 622 C 93033 DIM8

471 322 811 932 ED8 B


Light altering devices




413 03 01 B HONEYCOMB 50 B




413 03 02 LINEAR SPREAD LENS 50



413 03 03 SPREAD LENS 50




413 03 04 SOFTENING LENS 50



413 03 05 GLASS SBL 50

Finish your product



414 01 00 B SPY TUBE B

414 01 00 FBR SPY TUBE FBR

414 01 00 FG SPY TUBE FG

414 01 00 MMAT SPY TUBE MMAT

414 01 00 SG SPY TUBE SG

414 01 00 W SPY TUBE W

DELTALIGHT

PUNK 622 C 93033 DIM8

471 322 811 932 ED8 B

Notes: