



## SPYCO ON 2 93033 DIM8

414 353 812 932 ED8 B

AVAILABLE IN

**BLACK** 414 353 812 932 ED8 B

**WHITE** 414 353 812 932 ED8 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted, Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 350° rotatable
<b>INFORMATION</b>	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	C
<b>CERTIFICATES</b>	CB, EAC, ENEC, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm)
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1574lm // 11,6W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1130lm // 13,3W // 85lm/W

### Requirements

SPY TUBE S

For detailed installation instructions, please consult the manual : [414\\_353\\_812\\_XXX\\_ED8\\_HAND.pdf](#)

# DELTALIGHT


## SPYCO ON 2 93033 DIM8

414 353 812 932 ED8 B

### FINISH YOUR SPECIFICATION

#### Finish your product

---



**414 02 00 B**

SPY TUBE S B

**414 02 00 FBR**

SPY TUBE S FBR

**414 02 00 FG**

SPY TUBE S FG

**414 02 00 MMAT**

SPY TUBE S MMAT

**414 02 00 SG**

SPY TUBE S SG

**414 02 00 W**

SPY TUBE S W

Notes: