



## SUPER-OH! XS 25 DIM8

308 21 02 83 ED8 B

AVAILABLE IN

**BLACK** 308 21 02 83 ED8 B

**WHITE** 308 21 02 83 ED8 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted, Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.PC SBL

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	F

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 13,5W / CRI>80 / 3000K / 1470lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	1470lm // 13,5W // 109lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	691lm // 15,5W // 45lm/W

For detailed installation instructions, please consult the manual : [308\\_21\\_02\\_XX\\_ED8\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION

### Miscellaneous control equipment

### # of Fixtures




# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## SUPER-OH! XS 25 DIM8


308 21 02 83 ED8 B



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



**300 90 126** FALLING EDGE DIMMER 200W DIM2

Dimtype: DALI or push button

Cutout dimension (mm): 67

16



Notes: