





SUPER-OH! XS PIVOT 25 ADM DIM8

308 22 02 83 ADM ED8 B

AVAILABLE IN

BLACK 308 22 02 83 ADM ED8 B

WHITE 308 22 02 83 ADM ED8 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 45° swiveling, 350° rotatable
INFORMATION	INCL.PC SBL 3F MULTI ADAPTER

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 13,5W / CRI>80 / 3000K / 1470lm
LED TECHNICS (LIGHT SOURCE)	1470lm // 13,5W // 109lm/W
LED TECHNICS (LUMINAIRE)	691lm // 15,5W // 45lm/W

Requirements

TRACK 3F DIM

For detailed installation instructions, please consult the manual : [308_22_02_XX_ADM_ED8_HAND.pdf](#)

COMPATIBLE TRACKS

TRACK 3F DIM H

200 14 410 TRACK 3F DIM H 1m

1000 m 1.6 kg



200 14 420 TRACK 3F DIM H 2m

















2000 m 3.2 kg



DELTALIGHT

SUPER-OH! XS PIVOT 25 ADM DIM8

308 22 02 83 ADM ED8 B

200 14 430 TRACK 3F DIM H 3m	3000 m	4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410 TRACK 3F DIM IN 1m	1000 m	1.2 kg	 
200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	 
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	  
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	  
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	  

Notes: