



## SUPER-OH! XS PIVOT 39 DIM8

308 22 03 83 ED8 B

AVAILABLE IN

**BLACK** 308 22 03 83 ED8 B

**WHITE** 308 22 03 83 ED8 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.4
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 360° rotatable
<b>INFORMATION</b>	INCL.PC SBL

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 25W / CRI>80 / 3000K / 2940lm
<b>LED TECHNICS (LUMINAIRE)</b>	1396lm // 28,8W // 49lm/W

For detailed installation instructions, please consult the manual : [308\\_22\\_03\\_XX\\_ED8\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION

### Miscellaneous control equipment



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


### # of Fixtures

Min current | Max current

# DELTALIGHT

## SUPER-OH! XS PIVOT 39 DIM8

308 22 03 83 ED8 B




**300 90 004 ED8** WIRELESS CONTROL DIM8



**Dimtype:** WDL = wireless dimmable

**Cutout dimension (mm):** 40



**300 90 126** FALLING EDGE DIMMER 200W DIM2

8



**Dimtype:** DALI or push button

**Cutout dimension (mm):** 67

Notes: