





SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B

AVAILABLE IN
BLACK 418 162 822 MDL B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	DOWN : LENS FL-20° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED array 4,1W / CRI>80 / 2700K / 420lm UP: 2,1W / CRI>80 / 2700K / 213lm
SDCM	SDCM2
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	DOWN: 420lm // 4,1W // 103lm/W UP: 213lm // 2,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 328lm // 4,7W // 70lm/W UP: 153lm // 2,4W // 64lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [418_162_8XX_MDL_HAND.pdf](#)

DELTALIGHT

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B

FINISH YOUR SPECIFICATION


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

26

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

26

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

12

Dimtype: non-dimmable


Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

14


Dimtype: non-dimmable



300 89 48 150 LED POWER SUPPLY 48V-DC / 150W

21

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN


33

Dimtype: non-dimmable

DELTALIGHT

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B




21012 0230 LED POWER SUPPLY 48V-DC / 100W

14



Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

28




Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SUPERLOOP HC MDL


Available Colours




418 481 07 SUPERLOOP HC 70 MDL



418 481 09 SUPERLOOP HC 90 MDL



418 481 12 SUPERLOOP HC 120 MDL




418 481 17 SUPERLOOP HC 170 MDL



SUPERLOOP HC MDL XL

Available Colours



20555 0000 SUPERLOOP HC 200 MDL




20556 0000 SUPERLOOP HC 250 MDL




DELTALIGHT

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL


418 162 822 MDL B




20557 0000 SUPERLOOP HC 300 MDL



20558 0000 SUPERLOOP HC 350 MDL



20559 0000 SUPERLOOP HC 400 MDL




20560 0000 SUPERLOOP HC 500 MDL




SUPERLOOP S HC MDL


Available Colours




418 482 106 SUPERLOOP S HC 106 MDL



418 482 109 SUPERLOOP S HC 109 MDL



418 482 211 SUPERLOOP S HC 211 MDL



418 482 217 SUPERLOOP S HC 217 MDL



Notes: