



SUPERLOOP HC 350 SBL 930

20552 9300 FBR



AVAILABLE IN

BLACK 20552 9300 B

FLEMISH BRONZE 20552 9300 FBR

FLEMISH GOLD 20552 9300 FG

WHITE 20552 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	11.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL 4 SEGMENTS EXCL.LED POWER SUPPLY 24-DC INCL.8 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.4 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED FLEX FP 40,5W / CRI>90 / 3000K / 4900,5lm)
LED TECHNICS (LIGHT SOURCE)	19602 lm // 162 W // 121 lm/W
LED TECHNICS (LUMINAIRE)	8821lm // 186,3W // 47lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20552_XXX0_HAND.pdf](#)




FINISH YOUR SPECIFICATION

Current supply

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐

LED power supplies











of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '!' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	<u>300 89 24 60</u> LED POWER SUPPLY 24V-DC / 60W Dimtype: non-dimmable Cutout dimension (mm): 55	1/4 ☐
	<u>300 89 24 61</u> LED POWER SUPPLY 24V-DC / 60W DIN Dimtype: non-dimmable	1/4 ☐
	<u>300 89 24 80 ED1</u> LED POWER SUPPLY 24V-DC / 80W DIM1 Dimtype: 1-10V Cutout dimension (mm): 75	1/4 ☐

DELTALIGHT

SUPERLOOP HC 350 SBL 930







20552 9300 FBR

	<u>300 89 24 150</u> LED POWER SUPPLY 24V-DC / 150W	2/4	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 75		
	<u>300 89 24 480</u> LED POWER SUPPLY 24V-DC / 480W DIN	2	☐
	Dimtype: non-dimmable		
	<u>300 90 003 ED1</u> 24V-DC / 4A DIM1 UNIT	1/3	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	<u>300 90 003 ED5</u> 24V-DC / 4A DIM5 UNIT	1/3	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	<u>300 90 010</u> 24V-DC / 2 x 4A WIRELESS DIM UNIT	2/3	☐
	Dimtype: WDL = wireless dimmable		
	<u>21012 0101</u> LED POWER SUPPLY 24V-DC / 60W IP67 DIM1	1/4	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 65		
	<u>21012 0111</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM1	1/4	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 75		
	<u>21012 0121</u> LED POWER SUPPLY 24V-DC / 120W IP67 DIM1	2/4	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 75		
	<u>21012 0135</u> LED POWER SUPPLY 24V-DC / 60W IP67 DIM5	1/4	☐
	Dimtype: DALI		
	Cutout dimension (mm): 65		
	<u>21012 0145</u> LED POWER SUPPLY 24V-DC / 90W IP67 DIM5	1/4	☐
	Dimtype: DALI		
	Cutout dimension (mm): 75		


DELTA LIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FBR

	21012 0155 LED POWER SUPPLY 24V-DC / 120W IP67 DIM5	2/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 75	
	21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1	1/4 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 61	
	21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1	1/4 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 70	
	21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1	2/4 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 70	
	21012 0205 LED POWER SUPPLY 24V-DC / 60W DIM5	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 61	
	21012 0225 LED POWER SUPPLY 24V-DC / 100W DIM5	1/4 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 70	

Miscellaneous control equipment	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current






	300 90 24 ED2 LED DIMMODULE 24V / 3CH / 6A DIM2	2/4 ☐
	Dimtype: DALI or push button	

DELTALIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FBR



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐


DELTALIGHT

SUPERLOOP HC 350 SBL 930


20552 9300 FBR

	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
		Cutout dimension (mm): 27	
	<u>15225 0340 W</u>	SUSPENSION ST W	☐

Electric connection parts

	<u>328 10 03</u>	CONNECTION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	<u>15225 0360 B</u>	CONNECTION ST B	☐
		Cutout dimension (mm): 43	
	<u>15225 0360 W</u>	CONNECTION ST W	☐

DELTALIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FBR

Notes: