



Image may differ from the actual product  
Consult drawing for correct size

## SUPERLOOP HC 90 SBL 930

321 109 93 W



AVAILABLE IN

**BLACK** 321 109 93 B

**FLEMISH BRONZE** 321 109 93 FBR

**FLEMISH GOLD** 321 109 93 FG

**WHITE** 321 109 93 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	3
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.PC SBL EXCL.LED POWER SUPPLY 700-900mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm <sup>2</sup>

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 28,2-39W / CRI>90 (R9: 59) / 3000K / 3888-5160lm
<b>SDCM</b>	SDCM3
<b>LM80</b>	L70 > 30000
<b>LED TECHNICS (LIGHT SOURCE)</b>	5160lm // 39W // 132lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	3101lm // 44,8W // 69lm/W

### Requirements

LED POWER SUPPLY 700 / 900mA-DC DIM  
SUPERLOOP POWERBOX L/H 700mA  
SUPERLOOP POWERBOX H 900mA

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [321\\_X09\\_93\\_HAND.pdf](#)


# DELTALIGHT

## SUPERLOOP HC 90 SBL 930

321 109 93 W

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W



**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W


#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**321 55 207 ED1 B** SUPERLOOP POWERBOX L 700mA DIM1 B

1

Dimtype: 1-10V

**321 55 207 ED1 W** SUPERLOOP POWERBOX L 700mA DIM1 W

1



**321 55 309 ED5 B** SUPERLOOP POWERBOX H 900mA DIM5 B

1

Dimtype: DALI


**321 55 309 ED5 W** SUPERLOOP POWERBOX H 900mA DIM5 W

1

# DELTALIGHT

## SUPERLOOP HC 90 SBL 930

321 109 93 W



**20548 0015 B** SUPERLOOP POWERBOX H9 900mA DIM5 B

1

Dimtype: DALI

**20548 0015 W** SUPERLOOP POWERBOX H9 900mA DIM5 W

1


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 128** LED POWER SUPPLY 700mA-DC / 36W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 54




**300 90 129** LED POWER SUPPLY 900mA-DC / 60W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 84




**300 90 131** LED POWER SUPPLY 700mA-DC / 38W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 54


### Coversets



**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W



**204 00 90 ANO** COVERSET R 90 ANO


# DELTALIGHT

## SUPERLOOP HC 90 SBL 930

321 109 93 W

**204 00 90 B** COVERSET R 90 B


**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B


**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO

**204 80 80 B** COVERSET S 80 B

**204 80 80 W** COVERSET S 80 W



**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B

**204 90 90 W** COVERSET S 90 W

# DELTALIGHT

## SUPERLOOP HC 90 SBL 930

321 109 93 W

### Suspension parts


---



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0340 B** SUSPENSION ST B


Cutout dimension (mm): 27

---

**15225 0340 W** SUSPENSION ST W

### Electric connection parts

---



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43

---

**15225 0360 W** CONNECTION ST W

Notes: