




SUPERLOOP POWERBOX H8 700mA DIM5

321 55 307 ED5 W

AVAILABLE IN

BLACK 321 55 307 ED5 B

WHITE 321 55 307 ED5 W



 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.019
INFORMATION	Suited for 2 or 3 cable suspension INCL.DIMMABLE LED POWER SUPPLY 700mA / 38W $\lambda > 0,9$ Inrush current : 5A - 50 μ s @ 230V-AC Max. 50 units on circuit breaker B 16A

Electrical info

CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI

For detailed installation instructions, please consult the manual : [321 55 307_ED5_HAND.pdf](#)

WHERE USED

321 107 92	SUPERLOOP HC 70 SBL 927
321 107 93	SUPERLOOP HC 70 SBL 930
321 207 93	SUPERLOOP HC 70 SPR 930
321 209 93	SUPERLOOP HC 90 SPR 930
321 507 92	SUPERLOOP VC 70 SBL 927
321 507 93	SUPERLOOP VC 70 SBL 930
321 509 92	SUPERLOOP VC 90 SBL 927
321 509 93	SUPERLOOP VC 90 SBL 930
20561 9200	SUPERLOOP PLUS HC 70 SBL 927
20561 9300	SUPERLOOP PLUS HC 70 SBL 930
20570 9200	SUPERLOOP HC SBL OVAL S 927
20570 9300	SUPERLOOP HC SBL OVAL S 930
20572 9200	SUPERLOOP SLIM IN 70 SBL 927
20572 9300	SUPERLOOP SLIM IN 70 SBL 930
20573 9200	SUPERLOOP SLIM IN 90 SBL 927
20573 9300	SUPERLOOP SLIM IN 90 SBL 930
20576 9200	SUPERLOOP SLIM OUT 70 SBL 927
20576 9300	SUPERLOOP SLIM OUT 70 SBL 930
20577 9200	SUPERLOOP SLIM OUT 90 SBL 927
20577 9300	SUPERLOOP SLIM OUT 90 SBL 930
20580 9200	SUPERLOOP SLIM DOWN 70 SBL 927

DELTALIGHT

SUPERLOOP POWERBOX H8 700mA DIM5

321 55 307 ED5 W

20580 9300 SUPERLOOP SLIM DOWN 70 SBL 930

Notes: