





## SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B

AVAILABLE IN

**BLACK** 274 96 12 26 ED5 B

**WHITE** 274 96 12 26 ED5 W



[View on website](#)



### General info

|                           |  |
|---------------------------|--|
| <b>LOCATION</b>           | indoor   |
| <b>INSTALLATION</b>       | Ceiling Suspended  |
| <b>INGRESS PROTECTION</b> | IP20   |
| <b>WEIGHT (KG)</b>        | 21   |
| <b>ADJUSTABILITY</b>      | non adjustable   |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY - DALI (DT6)<br>CABLING 2 CIRCUITS<br>4 DALI CONTROL CHANNELS<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m<br>INCL.1 x CABLE 5 x 0.75mm <sup>2</sup> |

### Electrical info

|                     |                      |
|---------------------|----------------------|
| <b>ELECTRICAL</b>   | 120-240V / 0 50-60Hz |
| <b>CLASS</b>        | I                    |
| <b>POWER SUPPLY</b> | YES                  |
| <b>DIM TYPE</b>     | DALI                 |
| <b>ENERGY CLASS</b> | F                    |
| <b>CERTIFICATES</b> | CB, ENEC, EPD, RCM   |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | DOWN @ 2700K : LED cluster 179W / CRI>80 / 2700K - 5700K / 16942lm<br>UP @ 2700K : LED cluster 50W / CRI>80 / 2700K - 5700K / 4122lm<br>Or<br>DOWN @ 5700K : LED cluster 179W / CRI>80 / 2700K - 5700K / 19338lm<br>UP @ 5700K : LED cluster 50W / CRI>80 / 2700K - 5700K / 4530lm |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN @ 2700K: 16942 lm // 179 W // 95 lm/W<br>UP @ 2700K: 4122 lm // 50 W // 82 lm/W<br>Or<br>DOWN @ 5700K: 19338 lm // 179 W // 108 lm/W<br>UP @ 5700K: 4530 lm // 50 W // 91 lm/W  |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN @ 2700K: 13469lm // 205,8W // 65lm/W<br>UP @ 2700K: 3603lm // 57,5W // 63lm/W<br>Or<br>DOWN @ 5700K: 15316lm // 205,8W // 74lm/W<br>UP @ 5700K: 3959lm // 57,5W // 69lm/W   |

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

# DELTALIGHT

## SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B

For detailed installation instructions, please consult the manual : [274\\_96\\_12\\_26\\_ED5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W




**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W

#### Coversets



**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W



**204 00 90 ANO** COVERSET R 90 ANO

# DELTALIGHT

## SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B

**204 00 90 B** COVERSET R 90 B

**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B

**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B

**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO

**204 80 80 B** COVERSET S 80 B

**204 80 80 W** COVERSET S 80 W



**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B

**204 90 90 W** COVERSET S 90 W


# DELTALIGHT

## SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B

### Suspension parts


---



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0340 B** SUSPENSION ST B


Cutout dimension (mm): 27

---

**15225 0340 W** SUSPENSION ST W

### Electric connection parts

---



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43

---

**15225 0360 W** CONNECTION ST W

Notes: