





SUPERNOVA LINE 65 TW DOWN-UP DIM5

274 96 06 26 ED5 B

AVAILABLE IN

BLACK 274 96 06 26 ED5 B

WHITE 274 96 06 26 ED5 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	7.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT6) CABLING 2 CIRCUITS 4 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²
Electrical info	
ELECTRICAL	120-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K : LED cluster 45W / CRI>80 / 2700K - 5700K / 4208lm UP @ 2700K : LED cluster 17W / CRI>80 / 2700K - 5700K / 1374lm Or DOWN @ 5700K : LED cluster 45W / CRI>80 / 2700K - 5700K / 4841lm UP @ 5700K : LED cluster 17W / CRI>80 / 2700K - 5700K / 1510lm
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 4208 lm // 45 W // 93 lm/W UP @ 2700K: 1374 lm // 17 W // 81 lm/W Or DOWN @ 5700K: 4841 lm // 45 W // 108 lm/W UP @ 5700K: 1510 lm // 17 W // 89 lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 3131lm // 51,8W // 60lm/W UP @ 2700K: 1201lm // 19,6W // 61lm/W Or DOWN @ 5700K: 3592lm // 51,8W // 69lm/W UP @ 5700K: 1320lm // 19,6W // 68lm/W
Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

DELTALIGHT

SUPERNOVA LINE 65 TW DOWN-UP DIM5

274 96 06 26 ED5 B

For detailed installation instructions, please consult the manual : [274_96_06_26_ED5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W

Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

DELTALIGHT

SUPERNOVA LINE 65 TW DOWN-UP DIM5

274 96 06 26 ED5 B

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B

204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B


204 90 90 W COVERSET S 90 W

DELTALIGHT

SUPERNOVA LINE 65 TW DOWN-UP DIM5


274 96 06 26 ED5 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: