





TIGA IN LED 93024 DIM8

223 753 811 932 ED8 W-W

AVAILABLE IN

BLACK-FLEMISH GOLD 223 753 811 932 ED8 B-FG

WHITE-WHITE 223 753 811 932 ED8 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	423lm // 6,7W // 63lm/W

Accessories

TIGA V-PLATE

For detailed installation instructions, please consult the manual : [223_753_811_XXX_ED8_HAND.pdf](#)


DELTALIGHT

TIGA IN LED 93024 DIM8

223 753 811 932 ED8 W-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Light altering devices



223 753 01 B TIGA V-PLATE B

223 753 01 W TIGA V-PLATE W

Notes: