
DELTALIGHT®




TOPIX L X WW A

304 17 52 A

AVAILABLE IN
ALU GREY 304 17 52 A
GREY BROWN 304 17 52 G





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED array 3,5W / CRI>80 / 3000K / 478lm UP: LED array 3,5W / CRI>80 / 3000K / 478lm
LED TECHNICS (LIGHT SOURCE)	DOWN: 478lm // 3,5W // 137lm/W UP: 478lm // 3,5W // 137lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 67lm // 4W // 17lm/W UP: 170lm // 4W // 42lm/W

For detailed installation instructions, please consult the manual: **304_17_52_HAND.pdf**

DELTALIGHT®

TOPIX L X WW A

304 17 52 A

Notes: