



TOPIX WW



REFERENCE

304 17 02 A

AVAILABLE IN

ALU GREY 304 17 02 A

WHITE 304 17 02 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Wall Surface mounted
CUTOUT SHAPE/SIZE (MM)	round - 41
RECESSED DEPTH (MM)	38
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 1W / CRI>80 (R9: 6) / 3000K / 132lm)
TM-30 VALUES	Rf: 86 / Rg: 95
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	264lm // 2W // 132lm/W
LED TECHNICS (LUMINAIRE)	34lm // 2,3W // 15lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

CONCRETE BOX 153

CONCRETE BOX TR 154

For detailed installation instructions, please consult the manual : [304_17_01_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2->7

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2->7

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2->7

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2->7

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 60 LED POWER SUPPLY MULTI-POWER DIM7

6 | 0 | 0

Dimtype: 1-10V or push button

Cutout dimension (mm): 70




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

8

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

13(12)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82













300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

2->9(7)

Dimtype: 1-10V or push button











Cutout dimension (mm): 72

	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	2->7 ☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	8(7) ☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	4->20(19) ☐
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non-dimmable Cutout dimension (mm): 40	7(5) ☐
	300 90 104 LED POWER SUPPLY 350mA-DC / 6W	2 ☐
	300 90 112 LED POWER SUPPLY 350mA-DC / 18W Dimtype: mains (phase cut-off)	7 ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	3->8(7) ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2->8(7) ☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	9->14 ☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	3->7 ☐


DELTALIGHT

TOPIX WW

304 17 02 A

	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	2->9 ☐
Dimtype: 1-10V		
Cutout dimension (mm): 54		
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	2->9 ☐
Dimtype: DALI		
Cutout dimension (mm): 54		
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	12(12) ☐
Dimtype: WDL = wireless dimmable		
Cutout dimension (mm): 84		
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	2->9 ☐
Dimtype: WDL = wireless dimmable		
Cutout dimension (mm): 54		
	<u>21012 0258</u> LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	3->5 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 50		
	<u>21012 0268</u> LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	5->7 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 50		
	<u>21012 0298</u> LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	7 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 48		
	<u>21012 0308</u> LED POWER SUPPLY 350mA / 7,35W DIM8	2->3 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 40		
	<u>21012 0480</u> LED POWER SUPPLY 350mA-DC / 17W IP68	8(7) ☐
Dimtype: non-dimmable		
Cutout dimension (mm): 60		
	<u>21032 0295</u> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	7 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		


Concrete boxes



302 20 21 CONCRETE BOX 153



Cutout dimension (mm): 43 x 43



302 20 22 CONCRETE BOX TR 154



Cutout dimension (mm): 43 x 43

Notes: