





## XY180 S81 DIM1

422 111 93 ED1 B

AVAILABLE IN  
**BLACK** 422 111 93 ED1 B



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.9
<b>ADJUSTABILITY</b>	0° to 180° swiveling, 360° rotatable
<b>INFORMATION</b>	INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 0 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	1-10V
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED flex 8,9W / CRI>90 / 3000K / 1050lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	1050lm // 8,9W // 118lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	874lm // 10,2W // 85lm/W

### Remarks

[Look at the XY180 brochure](#)

### Options

XY180 CONNECTION BOX  
COVERSET R 90-100

For detailed installation instructions, please consult the manual : [422\\_111\\_XX\\_ED1\\_HAND.pdf](#)


## XY180 S81 DIM1

422 111 93 ED1 B

### FINISH YOUR SPECIFICATION

#### Miscellaneous control equipment

---




**300 90 016 ED1** WIRELESS CONTROL 5A DIM1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

#### Coversets


---



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B

**204 00 90 W** COVERSET R 90 W




**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B

**204 00 100 W** COVERSET R 100 W

#### Other

---



**422 99 01 B** XY180 CONNECTION BOX B

Notes:

# DELTALIGHT

**XY180 S81 DIM1**

422 111 93 ED1 B